

Claims

1. A router or bridge device (4) characterized in that it comprises
5 -means (13) for connection to a first network (6) and means for connection to a second network (12);
-an application for selecting configuration parameters, wherein the application applies a template for presenting parameters to a user, said template being uploadable to said device.
10
2. Device according to claim 1, comprising a plurality of templates.
3. Device according to claim 2, wherein the application comprises means for generating a template selection display to a user.
15
4. Device according to claim 2 or 3, wherein the application comprises means for loading a template from at least one of: a host device connected to the second network, a server connected to the first network.
- 20 5. Device according to one of the claims 1 to 4, wherein said application is a web server provided with means for generating pages for display on a remote display.
6. Device according to claim 5, wherein said display is part of a host device
25 comprising a browser for accessing the pages and for interacting with a user for selection of the configuration parameters.
7. Device according to claim one of the claims 1 to 6, wherein the application is adapted to generate at least one configuration file based on at least one
30 template.
8. Device according to claim 7, comprising a factory default configuration.

9. Device according to claim 7 and 8, comprising a configuration predetermined by an Internet service provider.

- 5 10. Device according to claim 9, wherein a priority is established between a user configuration, an internet service provider configuration and a factory default configuration in that order and wherein a parameter required by device software not found in one configuration is taken from a lower priority configuration.